



CT Gasket & Polymer Co., Inc.

DEL 8819 Emmott Rd, Houston, TX 77040

MAIL P.O. Box 40940, Houston, TX 77240-0940

TEL (713) 856-8667 / (800) 299-1685

FAX (713) 856-7317

WEB [www.ctgasket.com](http://www.ctgasket.com)

## SBR – Cloth Inserted

### *TYPICAL PHYSICAL PROPERTIES*

| PHYSICAL PROPERTY   | UNITS            | VALUE             |
|---------------------|------------------|-------------------|
| Ply                 |                  | 1 Ply per 1/16"   |
| Chemical Definition |                  | Styrene Butadiene |
| Durometer           | <i>(Shore A)</i> | 65 +/-5           |
| Tensile Strength    | <i>(psi)</i>     | 400               |
| Elongation          | <i>(% Min)</i>   | N/A               |
| Low Temperature     | <i>°F</i>        | -20               |
| High Temperature    | <i>°F</i>        | 170               |
| Abrasion Resistance |                  | Good              |
| Oil Resistance      |                  | Poor              |
| Sunlight Aging      |                  | Poor              |

The physical properties shown above are typical, but they should not be used to set Quality Control Specification minimum requirements. Please see the CTG Chemical Resistance Guide for general chemical resistance and affect.